

In the claims:

Please amend the claims as shown below:

1. (Original) An apparatus for installation at shooting  
5 ranges, comprising:  
a housing (12) having a resilient top layer (24) and a  
flexible bottom layer (26), the layer (26) extending along an  
inclined bottom surface (28) and over an upwardly protruding  
support member (30) to a front side (34), the top layer (24)  
10 being attached to the layer (26) at the front side (34) to  
form a water-tight container (25);  
a stationary non-flowable material (16) tightly packed in the  
container (25) for adhering to projectiles that have  
penetrated through the top layer (24); and  
15 the inclined bottom surface (28) being inclined at an angle  
(20) relative to a horizontal plane (21), the angle (20) being  
less than an angle of repose (23) of the granulated material  
(16).
- 20 2. (Original) The apparatus according to claim 1 wherein the  
housing (12) is in operative engagement with a rectangular  
housing (14) filled with a granulated material (116) and  
having a resilient front layer (106) for permitting  
projectiles (117) to pass therethrough.
- 25 3. (Original) The apparatus according to claim 2 wherein the

housing (12) has a horizontal segment (50) disposed at an upper end (51) of the housing (12) and in front of the front layer (106), the segment (50) and the front layer (106) having a gap (52) defined therebetween.

5

4. (Original) The apparatus according to claim 1 wherein a supporting member (32) is placed on top of the member (30) and the member (32) extends an entire width (W) of the housing, the housing (12) has a dewatering means (36) disposed therein.

10

5. (Original) The apparatus according to claim 4 wherein the bottom layer (26) and the upper layer (24) is attached to the member (32).

15

6. (Original) The apparatus according to claim 2 wherein the housing (14) has a watertight bottom layer (120) extending upwardly on a portion of an inside of the front layer (106).

20

7. (Original) The apparatus according to claim 1 wherein the member (30) is substantially perpendicular to the bottom surface (28) and the bottom layer (26).

25

8. (Original) The apparatus according to claim 2 wherein the housing (14) has an L-shaped concrete wall (58) for supporting a lid (60).

9. (Original) The apparatus according to claim 8 wherein the lid (60) has a downwardly protruding protector (64).

10. (Original) The apparatus according to claim 1 wherein the  
5 apparatus has an inclined bullet diverter (302) disposed at  
below a set of targets (308).

11. (Original) The apparatus according to claim 1 wherein the  
housing (12) has a horizontal segment (50) disposed at an  
10 upper end (51) of the housing (12).

12. (Original) The apparatus according to claim 1 wherein the  
bottom layer (26) is attached to the box (12) and has an area  
(27) disposed outside the box (12).

15

13. (Original) The apparatus according to claim 1 wherein the  
bottom layer (26) extends in a direction to divert water  
therefrom.

20